

HAFCO-METALMASTER EB-330DSC



Swivel Head-Dual Mitre Metal Cutting Band Saw with Conveyor System

2 Blade Speed 36 - 72mpm, Dual Mitre Cuts Up To 60°, Quick Action Material Clamp, Includes Hydraulic Downfeed Control & In & Out Feed Conveyor System



HAFCO-METALMASTER Swivel Head-Dual Mitre Metal Cutting Band Saw with Conveyor System EB-330DSC



90 Degrees Cut



Swivel Head, 45 Degrees Left Cut




Swivel Head, 60 Degrees Right Cut




Control Panel



Out Feed Roller Table with Length Stop




Length Stop on Ball Bearing Slide with Flip Up Action



Dual Mitre Rotating Table on Ball Bearings



Quick Action Material Clamp Lever



Quick Action Lever For Material Setup




Quick Release Sliding Vice



Trigger Control



Adjustable Hydraulic Blade Feed Dial



Blade Tension Device with Gauge



Ball Bearing and Carbide Blade Guides



Blade Cleaning Brush




Coolant System

HAFCO-METALMASTER Swivel Head-Dual Mitre Metal Cutting Band Saw with Conveyor System EB-330DSC




Motor and Gearbox



Blade Guard Micro



Blade Cut Out Switch



Cutting Capacity Chart

Features

- 295 x 230mm rectangular capacity
- Control panel with "Auto", "Manual" & "Set-Up" modes
- Unique rotating table swivels with the cutting head on ball bearings
- Swivel head double mitre cut to 45° right & left, 60° right
- Quick action lock/release lever for swivel head
- Swivel head incorporates rotating
- Quick action vice release to change opening & closing position
- Quick-action clamping lever for repetition work
- Unique sliding vice design for dual mitre operation
- User friendly blade tension system with gauge
- Larger cutting capacity than conventional cold saws
- Adjustable length stop for repetition cutting
- Heavy-duty gear drive system
- 2 x blade speeds 36 - 72mpm
- Ball bearing blade guides ensures minimal blade clearance wear and increases blade life due to less friction
- Coolant system for cutting efficiency and blade life
- Adjustable hydraulic cylinder for auto feed
- Vibration free, low noise operation ensures clean & high precision cuts
- Machine stand with integrated cooling fitted as standard
- Made in Taiwan

Includes

- In & out feed roller conveyor system with stands
- Material length stop on ball bearing slide with flip over design

Specifications

ORDER CODE	B075
MODEL	EB-330DSC
Operation Type	Swivel Head - Dual Mitre
Round @ 90° (mm)	260
Round @ 45° (mm)	240
Round @ 60° (mm)	160
Square @ 90° (mm)	230
Square @ 45° (mm)	210
Square @ 60° (mm)	130

HAFCO-METALMASTER Swivel Head-Dual Mitre Metal Cutting Band Saw with Conveyor System EB-330DSC

Rectangle (W x H) @ 90° (mm)	295 x 230
Rectangle (W x H) @ 45° (mm)	225 x 210
Rectangle (W x H) @ 60° (mm)	160 x 130
Coolant System	Yes
Table Working Height (mm)	950
Cutting Head Beam Type	Manual
Cutting Head Beam Return	Manual Return
Cutting Head Down Feed Control	Adjustable Hydraulic
Vice Clamping Fixture	Manual - Quick Action
Bundle Cutting Fixture	~
Blade Steps / Speeds (M/Min)	36, 72
Blade Size (L x W x T) (mm)	2965 x 27 x 0.9
Motor Power (kW / hp)	1.2 / 1.6
Voltage / Amperage (V / amp)	415
Nett Weight (kg)	404