

HAFCO-METALMASTER PD-28



Industrial Pedestal Drill - Belt Drive

Table Rotates 360°



HAFCO-METALMASTER Industrial Pedestal Drill - Belt Drive PD-28



Quill Handle



Drilling Depth Stop Setting With Scale




Adjustable Safety Chuck Guard



16mm Drill Chuck



Safety Emergency Stop Switch




Cast Iron Tilting-Rotating Table



Belt Tension Adjustment



A Section Belt Drive System




Speed Chart



Safety Micro Switch On Belt Cover



Cast Iron Base With T Slot



On Off Switch



Parts Included



Left Side View



Front View

HAFCO-METALMASTER Industrial Pedestal Drill - Belt Drive PD-28

Description

If you are in the market for a superior quality industrial belt drive drilling machine with a capacity of Ø23mm, and need it to take some serious work load duration then this machine would definitely perform to the task. This PD-28 pedestal drill manufactured in Taiwan to precision engineering tolerance & excellence will certainly transform your drilling holes experience to the next level of expertise.

What makes this machine different from the others is that the casting have been made heavier & thicker walled, which in this case relates to a total weight of 102kg on this model, that is approximately 70% heavier to its rival in this range.

Therefore, this range of drilling machines offers all the basic feature necessities to outperform & outlast the competitor machines all day everyday.

Features

- Ideal for industrial workshop use
- Quiet A section V-belt drive system
- Quick action belt tensioning lever
- Adjustable safety drilling chuck guard with micro switch
- Safety micro switch on pulley guard
- Safety magnetic-type switch
- Emergency stop switch
- Rack & pinion table height adjustment with locking lever
- Thick walled column ensuring greater rigidity
- Table rotates 360°
- Drilling depth stop setting with scale
- T slotted work table
- 12 spindle speeds - 300, 390, 450, 550, 620, 720, 1130, 1200, 1340, 1730, 1860, 2360rpm
- 240V Fan-cooled motor rated for continuous use with overload protection
- Made in Taiwan

Includes

- Drill chuck & arbor
- Chuck key to suit
- Drill drift

Specifications

ORDER CODE	D160
MODEL	PD-28
Type - Bench / Pedestal	Pedestal
Duty Type	Industrial-Duty
Drilling Diameter Capacity (mm)	Ø23
Spindle Taper (MT)	2
Spindle Travel (mm)	83
Throat Depth (mm)	185
Quill Diameter (mm)	47
Collar Diameter (mm)	65
Column Diameter (mm)	80
Spindle To Table (mm)	645

HAFCO-METALMASTER Industrial Pedestal Drill - Belt Drive PD-28

Spindle To Base (mm)	1180
Table Shape	Square
Table Size (mm)	285 x 285
Work Light	~
Micro Switch On Pulley Guard	Yes
Drive Belt Type	A Section
Spindle Speed Steps (No.)	12
Spindle Speed Range (rpm)	300 - 2360
Motor Power (kW / hp)	0.75 / 1
Voltage / Amperage (V / amp)	240 / 10
Overall Height (mm)	1710
Nett Weight (kg)	98