

RADIUS MASTER RM-48B




Radius Master Bench Belt Grinder / Linisher - Series 2

50 x 1220mm Belt Size




RADIUS MASTER Radius Master Bench Belt Grinder / Linisher - Series 2 RM-48B



Side View




Features




Rotates in Seconds for the following Linishing Applications




Side View



Small Wheel Selection for Notching & Contouring



For Fine Sharpening or Fast Metal Removal



Hollow Grinding & Micro Finishing on 8 inch Precision Ground Wheel




Flat Grinding on Platen



Tilting Table for Contouring & Pipe Notching




Accurate Tracking Produces Sharp Corners on Quick Release Toolrest



Accurate Squaring & Chamfering




Internal Pipe Chamfering




External Pipe Chamfering



De burring & Finishing Irregular Shapes



Irregular Shapes




Accurate Notching

RADIUS MASTER Radius Master Bench Belt Grinder / Linisher - Series 2 RM-48B



Tilting Table for Contouring & Pipe Notching



Optional Platen Table (L097)

Description

The Best Knife Making Machines & Belt Grinding Machines In The World

Radius Master's unique design provides a multitude of functions via 7 work stations, each readily available in seconds and without tools, using an easy to operate index knob. Only the Radius Master brand of machines are capable of tracking the latest heavy duty polyester backed ceramic belts. 7 work stations provide a wide variety of surface finishing, intricate product de-burring, tube notching, profiling and precision sharpening of drills and cutters.

Radius Master provides accurate tracking performance, allowing notching into sharp corners for better product finishing and significant savings on consumables, such as belts and contact wheels.

Lightning fast belt changes, 7 work stations and 5 contact wheels result in savings of hours per day on many jobbing, restoration and prototype work.

Designed for engineers, fabricators, welders, fitters, balustrade and stainless specialists, foundries, toolmakers, knife makers, rural manufacturers, mechanics, restorers, aircraft engineers, medical equipment manufacturers, sculptors, model makers and manufacturers of many wood and plastic products.

The Radius Master multi station belt grinder can do it all!

Features

- 7 work stations, 5 contact wheels (Ø25-Ø200mm), side tilt for pipe notching - all instantly accessible
- Uses include contouring, squaring, facing, deburring (inside tube included), sharpening, all stainless finishes, texturing, micro finishing and polishing
- Outstanding tracking allows notching sharp corners at the very edge of the belt. 3 x Plus better belt life
- Dust proof switch and 10ft (3m) lead and plug provided
- Can be laid on its side for profiling pipe notching etc. Table tilts to 45°
- The only belt grinder that accurately and rigidly tracks the heaviest backed belts (essential in drill & cutter sharpening)
- Sealed bearings teflon gaskets - adjustable pivots give many years life expectancy - Designed from 35 years experience in belt grinding
- Internal, external and hollow grinding on 5 contact wheels
- Flat grinding in vertical and horizontal position
- Edge grinding on tool rest (tilts up 20° and down 45°)
- Slack belt grinding in horizontal and vertical positions
- Its accurate tracking is an unmatched asset in precision sharpening of small drills & cutters and allows the use of cut down belts to 8mm for finishing & deburring difficult contours.
- Tracking mechanism will never lose it's precision as vital pivots are sealed ball bearings

RADIUS MASTER Radius Master Bench Belt Grinder / Linisher - Series 2 RM-48B

- Deburring of tube inside and outside
- Performance and durability backed by a 2 year commercial warranty
- Unmatched accuracy, versatility, performance & durability
- 50 x1220mm belt (6 sec belt change)
- 240V 1.5kW MOTOR totally enclosed with overload protection
- 20 year life expectancy
- Made in Australia

Includes

- Tool rest
- Notching tilt table
- 1 x zirconia belt
- 5 contact wheels (Ø25-200mm)

Specifications

ORDER CODE	L096B
MODEL	RM-48B
Type	Belt Grinder / Linisher
Mounting Type - Bench / Pedestal	Bench
Includes Stand	~
Belt Size (mm)	50 x 1220
Belt Speed (fpm / mpm)	3000 / 914
Motor Speed (rpm)	1400
Motor Power (kW / hp)	1.5 / 2
Voltage / Amperage (V / amp)	240 / 10
Nett Weight (kg)	50