

HAFCO-WOODMASTER DS-1632



Drum Sander - Open End

400mm Single Pass & 800mm Double Pass Capacity




HAFCO-WOODMASTER Drum Sander - Open End DS-1632



Belt Tension Adjustment



Handle For Height Adjustment



Height Gauge



Sanding Wheel with Rollers



Variable Speed Dial



100mm Dust Outlet

Description

Manufactured in Taiwan

The DS-1632 wide drum sander offers a unique open end sanding system that provides a maximum of 800mm sanding capacity with two passes, with a generous height capacity of 127mm down to a minimum of 3.2mm.

This machine is constructed from high grade cast aluminium to enable portability from site to site with ease. Fitted to this machine as standard feature is a variable table feed dial enabling operator to finely adjust surface finish required. It is recommended by the manufacturer to use a dust extraction system (not included) please refer to optional accessories.

Features

- Open side configuration with sanding capacity (400mm with 1 Pass) & (800mm with 2 Passes)
- Variable feed speeds from 0.6-3 M/min to suit various sanding requirements and material widths
- Ø100mm diameter dust hood outlet
- Rugged aluminium drum supports frame
- Drum height is adjusted by turning a control hand wheel
- Depth scale provided on the drum support frame for accurate reading of height adjustment
- Conveyor belt tracking is easy to adjust
- Quality Taiwanese

HAFCO-WOODMASTER Drum Sander - Open End DS-1632**Includes**

- Stand

Specifications

ORDER CODE	L110
MODEL	DS-1632
Variable Table Feed Speed (m/min)	0.6 - 3
Sanding Drum Speed (rpm)	1720
Belt Size (mm)	2330 x 78
Drum Diameter (mm)	127
Maximum Material Width (mm)	400
Maximum Material Thickness (mm)	127
Minimum Material Thickness (mm)	3.2
Dust Collector Port Diameter (Qty x mm)	1 x Ø63.5
Feed Motor Power (hp)	1/8
Motor Power (kW / hp)	0.75 / 1
Voltage / Amperage (V / amp)	240 / 10
Floor Space (W x D x H) (mm)	1050 x 700 x 1545
Nett Weight (kg)	70