


EXCISION XDP-SW68

ISO 68 Slideway Lube Oil

5 Litre



EXCISION ISO 68 Slideway Lube Oil XDP-SW68

Description

XDP Slideway Oils are high performance slideway lubricants. They are recommended for both vertical and horizontal slideways and can be used for both metal and plastic slideways. Metalium Slideway Oils contain specialised additives to enhance the fluid load carrying capacity, providing quicker operation, reduced friction and less wear.

ISO grade: 68
Density (15°C): 0,88 g/ml
Viscosity (40°C): 68 cSt
Viscosity (100°C): 9 cSt
Viscosity Index: 106
Flash point: >230°C
Freezing point: -12°C
Test 4 balls 40 Kg/1hour: 0.35 mm diameter

Store the product in an area with controlled temperature between 5° C and 40° C.
Life in unopened packaging: 1 year

Features

- Chloride, nitrate and silicone free
- Very high adhesion on metallic surfaces avoiding noises and vibrations.
- Anti-wear and high extreme-pressure properties to enable its use in gearboxes and mechanical transmission for tool-machines.
- Excellent protection against corrosion and oxidation
- DIN 51517 part 3 CLP standardization meet

Specifications

ORDER CODE	O003A
Grade	ISO 68
Size (Litre)	5
Application	SLIDE WAY OIL
Suits	~