

EXCISION XDP-SW32

ISO 32 Slideway Lube Oil

5 Litre



EXCISION ISO 32 Slideway Lube Oil XDP-SW32

Description

XDP-SW32 is an oil based lubricant formulated with highly refined mineral oil and special additives for its use in guides sliders tool-machines. It contains friction modifiers, extreme-pressure additives and demulsifiers which offer unctuousness and facilitate the separation of the coolants. it can be also used in tool-machines gearboxes and mechanical transmission subjected to very high loads.

ISO grade: 32
Density (15°C): 0,85 g/ml
Viscosity (40°C): 32 cSt
Viscosity (100°C): 5.3 cSt
Viscosity Index: 96
Flash point: >200°C
Freezing point: -20°C
Test 4 balls 40 Kg/1hour: 0.35 mm diameter

Store the product in an area with controlled temperature between 5° C and 40° C.
Life in unopened packaging: 1 year

Features

- Suitable for CNC Laser Machines and Machine Tool slide ways
- Very high adhesion on metallic surfaces avoiding noises and vibrations.
- Anti-wear and high extreme-pressure properties to enable its use in gearboxes and mechanical transmission for tool-machines.
- Excellent protection against corrosion and oxidation
- DIN 51517 part 3 CLP standardization meet

Specifications

ORDER CODE	O003B
Grade	ISO 32
Size (Litre)	5
Application	SLIDE WAY OIL
Suits	CNC Laser Machines Machine Tools