

SCHEPPACH Basato 4



Wood Band Saw



SCHEPPACH Wood Band Saw Basato 4



Quick Release System for Changing Band Saw Blade.



250mm Depth of Cut x 375mm Wide




Large Cast Iron Table with Rigid Rip Fence Assembly



Table Tilt Range from 17° to +45°



Industrial Triple Top Bearing Guides for Simple and Accurate Setting.



Industrial Triple Bottom Bearing Guides also Included



Cabinet Base with Internal Wheels with a External Quick Action Foot Lever



Easy Manoeuvrability with Simple Foot Lever and Lifting Handle



Table Tilt

Description

Exceptional specification- modest cost outlay.

Professional users, serious home wood workers and educational training workshops will welcome the introduction of the Scheppach Basato 4 band sawing machine which offers an exceptional specification with modest outlay.

The Basato 4 emits nothing more than a low purr when in operation - making it ideal for even the smallest workshop but yet the cutting performance will satisfy even the most demanding user. It comes with two cutting speeds of 800 and 1200 M/min and working capacity of 250mm depth of cut x 375mm wide.

The most important work project can be tackled with the utmost of confidence.

Even at its maximum depth of cut the Basato 4 operates smoothly and reliably, always following the desired line of cut. The tempered precision 3-roller guide - both above and below the saw table - guarantees precise constant operation. This precision blade guiding system, together with the rigid adjustable fence (with magnifying glass and designed to be used either left or right of the sawblade) allows for a working tolerance to a tenth of a millimetre. Fence removal can be made from the top and therefore is quick and efficient.

SCHEPPACH Wood Band Saw Basato 4

Irrespective of timber selection, the performance of the Basato 4 never varies.

So - if you work projects demand the very best in a mid-range band saw, we look forward to welcoming you to the thousands of Basato users worldwide.

From the moment you remove the protective packaging you will know you have made the right choice.

Table Size 548 x 400mm

Table Adjustment -17° to 45°

Cutting Speed 800/1200 m/min

Features

- German design & technology
- Twin 3-roller precision blade guides ensure precise cuts
- Precision rip fence with magnifier. Conveniently inserted from above for right and left hand use
- Patented table tilting from -17° to 45° with precise hand setting control
- Large 548 x 400mm cast iron table
- Massive 250 x 375mm cutting capacity
- Solid rip fence with eyeglass for precise settings
- Accepts up to 30mm width of blade for deep ripping
- Quick release mechanism for quick blade change
- For smooth running, the balanced and polished band wheels are fitted with a rubber facing
- Two cutting speeds from 800 and 1200M/min
- 2HP 240V motor
- Cabinet base with storage facility and wheels assembly standard
- A precise mitre fence comes as standard

Specifications

ORDER CODE	W856
MODEL	Basato 4
Wheel Diameter (Ø) (mm)	380
Throat Capacity (mm)	375
Height Capacity (mm)	250
Table Size (mm)	548 x 400
Frame Type	Steel
Motor Power (kW / hp)	1.5 / 2
Voltage / Amperage (V / amp)	240 / 10
Blade Code (Suits)	W856A, W856B
Blade Size (L x W x T) (mm)	2895 x 12 x 0.65
Floor Space (W x D x H) (mm)	~
Nett Weight (kg)	108